









Lower San Joaquin River Project -Tenmile Slough Reach 30L (TS30L) Levee Improvement Project

Pre-Construction Information Meeting – April 7, 2025

Meeting Format







Information Stations

Lower San Joaquin River Project
Tenmile Slough Levee Project (TS 30L)
San Joaquin Area Flood Control Agency

Project Partners

- U.S. Army Corps of Engineers, Sacramento District (Federal)
- CA Central Valley Flood Protection Board (State)
- CA Department of Water Resources (State)
- San Joaquin Area Flood Control Agency (Local)












What's the Problem We're Trying to Solve?

- Levees along San Joaquin/Calaveras Rivers need improvements to meet federal standards
- Levees are the last defense against flooding
- North/Central Stockton
 - ~122K residents
 - ~\$28.7B in damageable property



Typical Levee Issues






Project Overview & Schedule

- \$1.95 billion Federal project
- Cost Share: 65% Fed; 25% state; 10% local
- Increases level of flood protection along Calaveras and San Joaquin Rivers and Delta-front
- Construction of First Planned Reach (TS30L): 2025-2026
- Designs Next Several Project Reaches (phased approach): 2025-2034
- Project Completion: 2039

Project Plan	
Cutoff Walls	23.7 miles
Seismic Fixes	1.1 miles
Levee Raises (between 1.4' - 4.0')	3.4 miles
New Setback Levee	1.3 miles
Geometry Improvements (levee reshaping)	4.5 miles
Erosion Protection	5.0 miles
New Levee	0.8 miles
Closure Structures (2 locations)	0.6 miles

Lower San Joaquin River Project Area & Components













Tenmile Slough Levee (TS 30L)

- "Dryland" levee
- ~1.1 mile long
- Separates the Brookside (landside) from Wright Elmwood Tract (waterside)
- Most at-risk levee reach in system













TS30L Construction Activities

- Degrade top-half of levee
- Install bentonite slurry cutoff wall
- Install erosion protection
- Reshape levee
- Install maintenance access roads



TS 30L Levee Design Cross-Section




Figure 4-1: Cutoff Wall Typical Plan

Note that the landside easement (right side) shown would be the minimum easement; landside easements would range from 10 feet to 20 feet from the levee toe.

Construction Equipment



Bulldozer with GPS





Excavator

Levee Degrade



Cutoff Wall Construction











Installed Cutoff Wall




Levee Reshaping/Erosion Protection

- Flatten the levee embankments to 3:1 slopes
- Construct 20' wide levee crown road
- Place rock slope protection on waterside
- Place aggregate on landside



Construction Trucks Haul Route

- Soil Borrow location to Tenmile Slough
 - Borrow Site(SEWD)Location to Tenmile Slough
 - Cardinal Avenue to Hwy 26
 - > Hwy 26 to Hwy 99
 - Hwy 99 to Crosstown Freeway
 - Crosstown Freeway to I-5 N
 - > I-5 N to W. March Lane
- Construction trucks will use middle lane on W. March Lane





Lower San Joaquin River
HAUL ROUTE - SEWD BORROW SITE TO TS30L SITE



Potential Construction Impacts

Potential Impact	Best Management Practice
Noise	✓ Limited work hours
Dust	✓ Water trucks✓ Street sweeper on paved access road
Vibration	 ✓ Pre-construction Property Surveys ✓ Vibration monitors ✓ Established vibration limits & remediation
Construction trucks on March Lane	✓ Middle lane usage only

Construction Schedule

- Two construction seasons (2025 & 2026)
- April 15-November 1 each year
- Construction Hours
 - Monday-Friday
 - 7 a.m. to 7 p.m.
 - Truck traffic: 8 a.m.-4:30 p.m.





Project Contacts

- <u>www.spk.usace.army.mil/Missions/Civil-Works/Lower-San-Joaquin-River/</u>
- <u>www.sjafca.org/maps/lower-san-joaquin-river-project</u>



Q&A



Information Stations

Lower San Joaquin River Project
Tenmile Slough Levee Project (TS 30L)
San Joaquin Area Flood Control Agency

Cutoff Wall Construction









Threats to Levee Stability

